



POITIERS SMOKE/30

PRODUCT USE

INSIDE

WALL TILES

SHOWER WALL

TONALITY VARIATION

Tono Uniforme

PACKING

,50 M2/CJ 7,61 Kg/CJ 0 CJ/PI 0 Kg/PI

PRODUCT DESCRIPTION

Product Composition: Ceramic

Due to the handmade production and the raw materials used in its production, the pieces may fluctuate size, texture, and tone.

These variations are inherent in the manufacturing process and gives the product a unique personality and unrepeatable characteristics.

INSTALATION RECOMENDATION AND PRODUCT CARE






It is recommended that installation be performed by a qualified professional. We don't recommend use of adhesives based on epoxy resin. Respect the drying time set by the manufacturer of the adhesive used.

Fill joints thoroughly using fine grain size materials, which will not scratch the surface of the part. Remove with water and a sponge all the excess product before it sets.

Adhesive recommended for the product: Mapei poducts

Tixobond

For initial and daily cleaning use a damp cloth and mild soap is recommended. Avoid using abrasive cleaners and media products acidic or alkaline cleaning.

Body Technical Specifications		Test Method	Standard Value	Pass/Fail
	Frost resistance	ISO 10545-12		
Surface Technical Specifications		Test Method	Standard Value	Pass/Fail
	Acids and alkalis resistance	ISO 10545-13		
	Crazing resistance	ISO 10545-11		
	Staining resistance	ISO 10545-14		
	Surface Quality	ISO 10545-2		